



## CP SPINDLE OIL

COTTON PICKER SPINDLE OIL

**Product Description:** CP SPINDLE OIL 10 is a light colored, low viscosity, naphthenic base oil used for cleaning and flushing spindles with minimum staining of cotton. CP SPINDLE OILS 22 and 46 are light colored, non-staining, naphthenic base oil with special additives to provide excellent protection against rust, oxidation and foaming.

### Features:

- Economical lubricants
- Provides clean free running spindles
- CP 22, and 46 provide excellent rust protection
- All grades are light in color to minimize cotton staining
- Economical hydraulic oil where antiwear additives are not required.

### Typical Uses:

- CP SPINDLE OIL 10- commonly called "spindle slick", is used for cleaning and removing cotton fibers from spindles.
- Water-oil mixtures are also used for this purpose. For water-oil mixtures recommend LSC AP Soluble Oil S-40
- CP SPINDLE OIL 22 is recommended for lubrication of cotton pickers using drip lubricating systems.
- CP SPINDLE OIL 46 is recommended for lubrication of cotton pickers using flush lubricating systems.
- CP SPINDLE OIL 46 is also used as a "drip oil" for deep well pumps.
- CP SPINDLE OIL 46 is used as an in-expensive hydraulic oil where high oil consumption is a problem and anti-wear additives are not required.

### Typical Specifications:

GRADE, ISO	10	22	46
Gravity °API	29.2	24.7	24.5
Flash Point, °F.	320	340	360
Fire Point, °F.	245	370	400
Pour Point, °F.	-25	-20	-15
Viscosity:			
SUS @ 100 °F.	61	115	240
SUS @ 210 °F.	34	38.6	45.7
cSt. @ 40°C.	9.76	22	46
cSt@100°C.	2.41	3.65	5.8
Color, D-1500	2.0	2.5	2.5

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.