UNIVERSAL TRACTOR FLUID RED

PREMIUM TRANSMISSION-HYDRAULIC-WET BRAKE FLUID FOR TRACTORS



A PRODUCT OF LUBRICATING SPECIALTIES COMPANY

Product Description

UNIVERSAL TRACTOR FLUID RED is manufactured from premium high VI paraffinic base stocks that are fortified with inhibitors to help prevent rusting, foaming, oxidation, chatter, and wear. Other additives are used to protect rubber seals from excessive swelling or shrinking. Special friction modifiers are added to insure the proper operation of wet brakes and clutches.

It was developed for use in tractors and other farm implements having combination

transmission, differential, wet brake and hydraulic compartment.

Features & Benefits:

- Excellent wear protection and quiet, smooth operation.
- Superior thermal and oxidation stability compared to conventional ATF Fluids.
- Protects against rust and corrosion.
- Outstanding seal compatibility.
- Will not degrade nylon components.
- Dyed red to detect leaks.
- Multi-functional fluid Reduced inventory.
- Can be used as a Power Steering Fluid in all types of vehicles with exception of Honda and OEM specific.

Applications & Uses:

Recommended for:

- Deutz-Allis: 25743, 257541 & 246634 Hydra Trans Fluid
- Denison HF-0, HF-1 & HF-2.
- J.I. Case-JIC 143,144,145(TCH Fluid), 185(TSD Fluid), MS 1204,1205,1206(Powergard PFT), 1207(Hy-Tran Plus), 1210.
- John Deere: J20C, J14(A/B/CJDT303),J20(A/B, HyGard), J2.1 A & J27(10W or 30).
- Ford/New Holland M2C134-A/B/C/D, M2C86 A/B/C, M2C77-A, M2C53-A, M2C48-B/C, M2C41-B.
- International Harvester B-5, B-6 (Hy-Tran).
- Kubota UDT Hydraulic/Transmission Fluid.
- Massey-Fergusson M-1110, M-1127A & B, M-1129A (Permatran), M-1135 (Permatran III), M-1139, 114, 1143, & 1145.
- Oliver: Type 55, Type 5J, & Q 1802.
- Renk: Bus Automatic Trans Fluid.
- Steiger: HydraTrans Fluid.
- Sundstrand Hydrostatic Transmission Fluid.
- White Q-1705, 1722, 1766, 1766B(UTHF), 1802, & 1826
- Allison C-4.C-3.
- API GL-4.
- Caterpillar TO-2.
- Volvo, VME, VCE, (inc. latest Wet-Brake requirements).
- ZF TE-ML-03 and TE-ML-06.

Also meets OEMs such as Deutz, Fiat-Hesseton, Sauer Sunstrand/Danfoss, Versatile, Sperry Vickers/Eaton (I-2805 & M2950s)

Typical Test Data

TEST	ASTM	UTF
Gravity °API	D-4052	32.3
Flash Point, ° C.	D-92	216
Pour Point, ° C.	D-97	-39
Viscosity:		
cSt@100°C.	D-445	9.5
Brookfield Viscosity:		
сР@-30°F.	D-2983	70,000
сР @ -0° F.	D-5293	4,500
Viscosity Index	D-2270	136
Color		Red

* CONTAINS HIGH PERFORMANCE ADDITIVE CHEMISTRY. VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.

TECHNICAL PRODUCT INFORMATION

© 1928-2017 Lubricating Specialties Company. All rights reserved. LSC® Lubricating Specialties Company Hallmark is trademark owned by Lubricating Specialties Company. Lubricating Specialties Company | 562.776.4000 | www.lsc-online.com MADE IN U.S.A.