

UNITRAN ATF



A PRODUCT OF LUBRICATING SPECIALTIES COMPANY

Product Description

UNITRAN ATF is a general-purpose ATF manufactured from premium quality base oils and blended with a specifically balanced additive combination to provide high oxidation stability, excellent foam resistance, corrosion wear protection, and heat resistance. This complex fluid is also compounded with a friction-modifying additive to provide smooth lock-up of clutches without chatter.

This fluid is a general-purpose fluid that meets and exceeds all the old OEM specifications like MERCON, Allison and others.

Applications & Uses:

- Meets the Performance requirements of Ford.
- Meets the requirements for Allison C4 specifications.
- Recommended for most European OEM requirements.
- Recommended for use in General Motors Vehicles, where DEXRON VI products is not recommended.

Features & Benefits:

- Excellent wear protection and quiet, smooth operation.
- Superior thermal and oxidation stability.
- Protects against rust and corrosion.
- Outstanding seal compatibility.
- Dyed red to detect leaks.
- Multi-functional fluid - Reduced inventory.

Typical Test Data

TEST	ASTM	ATF
Gravity °API	D-4052	34.2
Flash Point, ° C.	D-92	220
Pour Point, ° C.	D-97	-51
Viscosity:		
<i>cP. @ -40° C., Brookfield</i>	D-2983	18,500
<i>cSt. @ 40° C.</i>	D-445	36.2
<i>cSt@100° C.</i>	D-445	7.50
Viscosity Index	D-2270	180
Color	----	Red

* CONTAINS HIGH PERFORMANCE ADDITIVE CHEMISTRY.
VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.

TECHNICAL PRODUCT INFORMATION

PRODUCT CODE: 33680

© 1928-2017 Lubricating Specialties Company. All rights reserved.
LSC® Lubricating Specialties Company Hallmark is trademark owned
by Lubricating Specialties Company.
Lubricating Specialties Company | 562.776.4000 | www.lsc-online.com
MADE IN U.S.A.

08.17