

PIRANHA 803 QUENCH OIL

PREMIUM HIGH-SPEED QUENCHING OIL



A PRODUCT OF LUBRICATING SPECIALTIES COMPANY

Product Description



803 QUENCH OIL is a premium high-speed quenching oil containing a balanced blend of base oils and additives to achieve maximum hardness of low-carbon or low alloy steels.

Applications & Uses:

- Recommended where maximum hardening power and fast quench are desired.
- Used for quenching low carbon or low alloy steels.
- Used for steel that has been heat treated in furnace of cyanide salt bath.

Features & Benefits:

- Superior oxidation stability.
- Very rapid quench - GMC Quench Test 10-11 seconds.
- Made from HVI paraffinic stocks

Typical Test Data

TEST, ISO GRADE	ASTM	803
Gravity, °API	D-4052	28.5
Flash Point, °C.	D-92	177
Pour Point, °C.	D-97	-15
Viscosity: cSt. @ 40°C.	D-445	23.5
Color	D-1500	3.0
GMC Quench Test, Seconds	----	10-11
Sulfated Ash, WT.%	D-874	0.50

* CONTAINS HIGH PERFORMANCE ADDITIVE CHEMISTRY.
VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.

TECHNICAL PRODUCT INFORMATION

PRODUCT CODE: 39014

© 1928-2017 Lubricating Specialties Company. All rights reserved.
LSC® Lubricating Specialties Company Hallmark is trademark owned
by Lubricating Specialties Company.
Lubricating Specialties Company | 562.776.4000 | www.lsc-online.com
MADE IN U.S.A.

08.17