

# RED-i<sup>®</sup> EXTREME PRESSURE GREASE

PREMIUM-TACKY-ADHESIVE-MULTI-PURPOSE EP GREASE DESIGNED TO “STAY IN PLACE AND LUBRICATE”  
IN THE MOST SEVERE WATER-WASHING AND SHOCK LOADING AUTOMOTIVE AND INDUSTRIAL APPLICATIONS



A PRODUCT OF LUBRICATING SPECIALTIES COMPANY

## Product Description



**RED-i<sup>®</sup> EP GREASE** is a premium, heavy duty, extreme pressure multipurpose lithium complex grease fortified with polymers, antiwear agents, tackiness additives, high viscosity base oils plus rust and oxidation inhibitors. This grease is designed to “stay-in-place and lubricate”

under the most severe operating conditions found in industrial and automotive service, it is unsurpassed in resisting water wash out and protecting against wear in shock loading applications.

**RED-i<sup>®</sup> EP GREASE** is the grease designed to “stay there and lubricate” under the worst conditions of water-dirt-mud.

### NOTE:

NOT RECOMMENDED FOR SMALL ANTI-FRICTION BEARINGS OPERATING OVER 5000 RPM.

TACKINESS ADDITIVES USED TO MAKE GREASE “STAY IN PLACE” MAKE THIS GREASE HARDER TO PUMP AND MAY REQUIRE THE USE OF A HEAVY FOLLOWER PLATE IN AIR OPERATED GREASE PUMPS. NOT RECOMMENDED FOR CENTRALIZED DISPENSING SYSTEMS COMMONLY FOUND IN INDUSTRIAL PLANTS UNLESS THEY ARE CAPABLE OF PUMPING A GREASE OF THIS TYPE.

## Applications & Uses:

- Recommended for wheel bearing, including disc brakes applications. Fifth wheel, U-joint, steering linkage and chassis lubrication.
- An ideal chassis lubricant for “on & off road” equipment in agriculture, construction, logging, trucking and mining service where severe water washing or shock loading protection is needed.
- Recommended for industrial plain bearings and antifriction bearings operating under shock-loads or wet and dirty conditions.

## Features & Benefits:

- Adhesive-tacky, grease that “stays in place and lubricates”.
- Unsurpassed water wash-out resistance due to high viscosity base oils fortified with polymers.
- Great protection against failures caused by shock loading.
- Extreme pressure protection - Exceeds 70 pounds OK Load in the ASTM D-2509 Timken Test.
- Critical metal surfaces of moving parts are protected from rust and corrosion.
- Distinctive red color quickly identifies the grease and helps detect defective bearing seals.
- Reduced maintenance expense because “stay-in-place and lubricate” attribute means less frequent greasing intervals and extended equipment life.
- Oxidation inhibitors permit operations at high temperatures for extended periods.
- NLGI #2 certified GC-LB in wheel bearing and chassis applications.

## Typical Test Data

TEST, NLGI GRADE	ASTM	1	2
Penetration @ 77 ° F.	D-217	310-340	265-295
Dropping Point, °F.	D-2265	500+	500+
Soap Type	----	Lithium Complex	Lithium Complex
Color	----	Red	Red
Appearance	----	Smooth and Tacky	Smooth and Tacky
Timken OK Load, Lb.	D-2509	70 lbs. Minimum	70 lbs. Minimum
Base Oil Viscosity:			
cSt. @ 40°C.	D-445	220	220
cSt. @ 100°C.	D-445	14.3	14.3
Water Washout Loss %	D-1264	6	5
4 Ball Wear Test:			
10kg @ 1800ppm, 75 °C, 1hr.	D-2266	0.28 mm.	0.28 mm.
40kg @ 1200rpm, 75 °C, 1hr.	D-2266	0.55 mm.	0.56 mm.

\* CONTAINS HIGH PERFORMANCE ADDITIVE CHEMISTRY.  
VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.

## TECHNICAL PRODUCT INFORMATION

PRODUCT CODE: 50041, 50042

© 1928-2017 Lubricating Specialties Company. All rights reserved.  
LSC<sup>®</sup> Lubricating Specialties Company Hallmark is trademark owned  
by Lubricating Specialties Company.  
Lubricating Specialties Company | 562.776.4000 | www.lsc-online.com  
MADE IN U.S.A.