

GRIZZLY GREASE III



A PRODUCT OF LUBRICATING SPECIALTIES COMPANY

Product Description

GRIZZLY GREASE III is a specially formulated rod grease designed exclusively for Summit Drilling Fluids. This product is the result of a two year research and development effort aimed at replacing Barium Greases which are harmful to the environment.

Extensive field tests confirm that **GRIZZLY GREASE III** is a very effective rod grease and its unique characteristics make it suitable for many other heavy duty lubrication applications.

Applications & Uses:

- Rod Grease.
- Rock crushers / oil field equipment.
- Heavy duty construction equipment.
- Offshore drilling equipment.

Features & Benefits:

- Excellent vibration dampening.
- Excellent water resistance.
- Good metal adhesion.
- Wide temperature range.

Typical Test Data

| TEST, NLGI GRADE | ASTM | 4 |
|-----------------------|--------|---------------------------|
| Penetration @ 77 ° F. | D-217 | 190 |
| Dropping Point, °F. | D-2265 | 390 |
| Timken OK Load, lbs. | ---- | 50 |
| Soap Type | ---- | Lith. 12-Hydroxy Stearate |
| Color | ---- | Blue |
| Texture | ---- | Smooth |
| Tackiness | ---- | Tacky |
| Water Washout, % Loss | ---- | Buttery |

* CONTAINS HIGH PERFORMANCE ADDITIVE CHEMISTRY.
VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.

TECHNICAL PRODUCT INFORMATION

PRODUCT CODE: 50168

© 1928-2017 Lubricating Specialties Company. All rights reserved.
LSC® Lubricating Specialties Company Hallmark is trademark owned
by Lubricating Specialties Company.
Lubricating Specialties Company | 562.776.4000 | www.lsc-online.com
MADE IN U.S.A.

08.17