PIRANHA HD DRAWING OIL

HEAVY DUTY DRAWING OIL CONTAINING EXTREME PRESSURE ADDITIVE



A PRODUCT OF LUBRICATING SPECIALTIES COMPANY

Product Description



HD DRAWING OIL straight oil is a heavy viscosity product formulated with mineral oil, extreme pressure additive and lubricating agent. It is excellent on ferrous and non-ferrous metals.

It can be used for drawing, forming, stamping, punching and other applications.

Applications & Uses:

- Recommended for:
 - Drawing
 - Tapping
 - Forming
 - Drilling
 - Sawing

Features & Benefits:

- Extreme pressure additive to extend tool and die life.
- Non staining additives for use with non-ferrous metals.
- Transparent for good visual control.

Typical Test Data

TEST	ASTM	RESULT
Gravity °API	D-4052	0.6
Flash Pt., °C.	D-92	177
Fire Pt., °C.	D-92	199
Viscosity:		
cSt. @ 40°C.	D-445	225
cSt.@ 100° C.	D-445	16.0
Color	D-1500	3.5

* CONTAINS HIGH PERFORMANCE ADDITIVE CHEMISTRY. VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.

TECHNICAL PRODUCT INFORMATION

© 1928-2017 Lubricating Specialties Company. All rights reserved. LSC® Lubricating Specialties Company Hallmark is trademark owned by Lubricating Specialties Company. Lubricating Specialties Company | 562.776.4000 | www.lsc-online.com MADE IN U.S.A.