



# PRODUCT INFORMATION

A product of Lubricating Specialties Company

## Technolube

MIL-PRF-17672E NAVY SYMBOL OILS ZINC FREE TURBINE/HYDRAULIC OIL

---

### Product Description

Manufactured from the highest quality solvent refined paraffinic base stocks. These products offer excellent resistance to oxidation and rust, superior water demulsibility properties, and are fortified with a very effective non zinc additive to provide outstanding wear protection.

---

### Advantages & Uses

- Intended for use in shipboard hydraulic systems not requiring the use of a fire resistant fluid. Also recommended for all types of gas or steam turbines (except those specifying extreme high temperature lubricants), air compressors, pumps, electric motor bearings, speed reducers, and as a general plain or antifriction bearing lubricant.

---

### Features

- Manufactured to meet MIL-PRF-17672E.

---

Test	2075 <sup>th</sup>	2110 <sup>th</sup>	2135 <sup>th</sup>
ISO VG	32	46	68
Viscosity Index	94	95	95
Flash Point °C (°F) –Min.	157 (315)	163 (325)	171 (340)
Pour Point °C (°F) –Max.	-29 (-20)	-23 (-10)	-18 (0)
Neutralization # -Max. D-974	0.20	0.20	0.02
% Water Content D-95	None	None	None
Foam Characteristics D-892			
Seq. #1 ML Max	65/0	65/0	65/0
#2 ML Max	65/0	65/0	65/0
#3 ML Max	65/0	65/0	65/0
Oxidation Test			
Time required to reach neutralization			
Value of 2.0 mg. KOH	1000 Hrs. +	1000 Hrs. +	1000 Hrs. +
Rust Preventative Characteristic D-665	Pass	Pass	Pass
Copper Strip Corrosion D-130	1 Max	1 Max	1 Max

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY