

Vistone A-30



A PRODUCT OF LUBRICATING SPECIALTIES COMPANY

Product Description

Vistone A-30 is a synthetic diester basestock for use in a wide range of high performance lubricants including crankcase oils and industrial oils.

Vistone A-30 is particularly suitable for use in compressor oils and hydraulic fluids. It is also useful in two-cycle engine lubricants and high temperature greases.

Applications & Uses:

- Recommended for use a component in rotary screw compressors.
- Shows major improvements in performance against mineral oils.
- Low deposits.
- Used in Single & Multi-stage reciprocating air compressors.
- Used in crankcase oils, hydraulic oils and two-cycle engines.

Features & Benefits:

- High film strength.
- Excellent oxidation resistance, thermal stability and solvency for improved cleanliness, increased service and filter life.
- Excellent air entrainment properties and good demulsibility properties.
- Wide operating temperature range providing high and low temperature protection.

Typical Test Data

TEST PARAMETERS	ASTM	ISO 32
Appearance		B&C
Color	D-1500	0.5
API Gravity	D-1298	23.1
Density @ 15 °C	D-1298	0.915
Flash Point, COC °C	D-92	235
Pour Point, °C	D-97	-54
Viscosity:		
cSt @ 40°C	D-445	27.1
cSt @ 100 °C	D-445	5.4
Viscosity Index	D-2270	138
Volatility, % off @ 240 °C		7
Total Acid Number, mgKOH/g	D-664	0.04
Water Content, ppm	D-1364	300

* CONTAINS HIGH PERFORMANCE ADDITIVE CHEMISTRY.
VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.

TECHNICAL PRODUCT INFORMATION

PRODUCT CODE: 37009

© 1928-2017 Lubricating Specialties Company. All rights reserved.
VISTONE® Compressor Fluids Hallmark is trademark owned
by Lubricating Specialties Company.
Lubricating Specialties Company | 562.776.4000 | www.lsc-online.com
MADE IN U.S.A.