

UNITRAN SYNTHETIC LO-VIS MVP ATF DEXRON® VI



A PRODUCT OF LUBRICATING SPECIALTIES COMPANY

Product Description

UNITRAN SYNTHETIC LO-VIS MVP ATF is a new Multi-Vehicle fluid manufactured from premium quality synthetic base oils blended with a specifically balanced additive combination to provide high oxidation stability, excellent foam resistance, corrosion and wear protection, and heat resistance. This complex fluid is also compounded with a friction-modifying additive to provide smooth lock-up of clutches without chatter.

It meets and exceeds some current original equipment manufacturers specifications for automatic transmission fluids, including GM, Ford, Toyota, Mitsubishi and others .

Features & Benefits:

- Excellent wear protection and quiet, smooth operation.
- Superior thermal and oxidation stability compared to conventional ATF Fluids.
- Protects against rust and corrosion.
- Outstanding seal compatibility.
- Will not degrade nylon components.
- Dyed red to detect leaks .
- Multi-functional Low viscosity ATF fluid – Reduced inventory.

Note: Not recommended where CVT fluids, Type F or Power Steering Fluids for Honda are specified.

Applications & Uses:

- ATF: Shell 3353 / 134 / M-1375.4 **; Audi / VW: G 052 533/ G 055-005 (A,A2) / G 055 540(A2) **
- Bentley: P/N PY112995PA**; BMW / Mini: PN 83220142516 / PN 83220397114 / 163514 / PN 83222152426**
- Chrysler / Dodge / Jeep: PN 05127382AA / PN 680433742AA / PN 68157995AA**
- **Ford MERCON® LV - License pending;** Ford / Lincoln / Mercury: PN XT-10-QLV (LV) / PN XT-6-QSP or DSP(SP)**
- **GM DEXRON® VI Approved - License NO. J-60194;** GM / GMC / Opel / Saturn: AW1 / PN 88863400 / PN 88863401**
- Honda / Acura: DW-1**; Hyundai / Kia: SP-IV / NWS-9638 T-5 / PN 040000C905G / SPH-IV**
- Jaguar: Fluid 8432**; JASO M315, Class 1A-LV
- Maserati: PN 231603 **; Mazda: FZ**; Mercedes Benz: MB 236.12; Mercedes / Daimler: MB 236.14/15/41**;
- Mitsubishi: Diaqueen ATF J-3
- Nissan: Matic S (backward compatible to Matic D / Matic J)
- Porsche: PN 000 043 304 00**
- Saab: 93 165 147 – AW-1, T-IV (JWS 3309)
- Toyota / Lexus / Scion: Type WS
- Volkswagen / Audi: G 055 162 (A2/A6) / G 060162 A1/A2/A6**

** Suitable for use.

Typical Test Data

TEST	Lo-Vis MVP ATF
Gravity, ° API	36.19
Pour Point, °C.	-48
Viscosity:	
cP. @ -40 °C., Brookfield	11,750
cSt. @ 40 °C.	31.25
cSt. @ 100 °C.	6.1
Viscosity Index	160
Color	Red
Phosphorus, wt %	0.016

* CONTAINS HIGH PERFORMANCE ADDITIVE CHEMISTRY.
VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.

TECHNICAL PRODUCT INFORMATION

PRODUCT CODE: 330049

© 1928-2017 Lubricating Specialties Company. All rights reserved.
LSC® Lubricating Specialties Company Hallmark is trademark owned
by Lubricating Specialties Company.
Lubricating Specialties Company | 562.776.4000 | www.lsc-online.com
MADE IN U.S.A.

05.17