

# SYN CVT FLUID

PREMIUM SYNTHETIC CVT FLUID FOR CONTINUOUSLY VARIABLE TRANSMISSIONS



A PRODUCT OF LUBRICATING SPECIALTIES COMPANY

## Product Description

**MULTI-VEHICLE CVT FLUID** is manufactured to meet Multi-Vehicle OEM specifications. It is formulated using premium quality synthesized Hydrocarbons blended with a specifically balanced additive combination to provide high oxidation stability, excellent foam resistance, corrosion and wear protection, and heat resistance. This complex fluid is also compounded with a friction-modifying additive to provide a smooth and efficient transmission.

This fluid is a multi-purpose CVT fluid that meets and exceeds all current original equipment manufacturers specifications for continuously variable transmission fluids, including some of the latest OEM specifications as specified by Audi, Mitsubishi, Nissan, Saturn, Subaru and Toyota.

## Applications & Uses:

- Used for both types (Chain and Push Belt) of CVTs for Service Fill for maximum engine size of 3.5L.
- Suitable for Use in the following Chain Type of CVT
  - Audi A4 & A6
- Suitable for Use in the following Belt Type of CVT
  - Mitsubishi-Lancer & Outlander; Nissan-Altima, Murano, Quest, Sentra SE-R, Versa SI; Saturn-Ion Quad Coupe/Vue; Subaru-Justy; Toyota-all non-hybrid CVTs.
- Meets the Performance-Toyota CVTF-TC/FE, Nissan NS-1 / NS-2 / NS-3, Mitsubishi CVTF J1, Honda HMMF / HCF2, Daihatsu AMMIX CVT, Subaru ECVT / CVT, Suzuki NS-2, BMW Mini Cooper EXL 799, Dodge / Jeep NS-2.

## Features & Benefits:

- Excellent wear protection and quiet, smooth operation for the CVT steel belts.
- CVTs are more fuel efficient versus traditionally 4-Speed Automatic Transmission (4-8%).
- Superior thermal and oxidation stability compared to conventional ATF / CVT Fluid.
- Protects against rust and corrosion.
- Outstanding seal compatibility and will not degrade nylon components.
- Multi-function fluid - will reduce inventory.
- Can be used as a Power Steering Fluid in all types of vehicles with exception.
- Synthetic Fluid to enhance drain intervals.

## Typical Test Data

TEST	ASTM	SYN CVT
Sp. Gravity	D-4052	0.8481
Gravity °API	D-4052	35.34
Flash Point, ° C.	D-92	215
Pour Point, ° C.	D-97	-40
Viscosity:		
cSt. @ 40° C.	D-445	34.77
cSt. @ 100° C.	D-445	7.06
Viscosity Index	D-2200	182
cP @ -40° C., Brookfield	D-2983	13,500
Color	D-1500	2.0

\* CONTAINS HIGH PERFORMANCE ADDITIVE CHEMISTRY.  
VALUES SHOWN HERE ARE TYPICAL AND MAY VARY.

## TECHNICAL PRODUCT INFORMATION

PRODUCT CODE: 33912

© 1928-2017 Lubricating Specialties Company. All rights reserved.  
LSC® Lubricating Specialties Company Hallmark is trademark owned  
by Lubricating Specialties Company.  
Lubricating Specialties Company | 562.776.4000 | www.lsc-online.com  
MADE IN U.S.A.

08.17